

What is claimed is:

1. A twine cutter comprising:

a plane frame, composed of four struts making an approximate rectangular shape,
enclosing a substantially rectangular opening, wherein said frame is
composed of strong material to handle rough cutting, and wherein said
opening serves as a hand holder for said cutter; and
a blade holder strut composed of strong material, complete with connected blade,
firmly attached to one end of said frame, wherein said blade is imbedded
at a diagonal angle in a recessed notch for safety.

2. The cutter according to claim 1 wherein said frame including said blade holder strut
further comprise one continuous injection molded piece of plastic.

3. The cutter according to claim 1 wherein said blade holder further comprises a
rounded pinch ending aligned nearly parallel to one long side of said frame to serve
as a device for hooking under a piece of twine to be then cut by said blade.

4. The cutter according to claim 1 wherein said hand holder further comprises a wavy
finger-fitting design in the inside opening of the long side of said frame opposite said
blade holder for improved hand contact.

5. The cutter according to claim 4 wherein said wavy finger-fitting design further com-
prises spacing of said design for small, medium and large hand sizes.

6. The cutter according to claim 1 wherein said hand holder further comprises sufficient
space that a large gloved hand is easily accommodated.

7. The cutter according to claim 1 further comprising an overall dimension that fits into
a coat pocket while still possessing sufficient size for easy hand operation.

8. The cutter according to claim 1 wherein said blade further comprises a high quality
steel material.

9. A twine cutter comprising:

a plane substantially rounded rectangular frame composed of strong injection molded plastic enclosing an elongated opening, wherein said opening serves as a hand holder for said cutter;

5

a blade holder strut composed of strong injection molded plastic complete with connected blade imbedded in a recessed notch for safety.; and

means for firmly attaching said blade holder to said frame on the opposite side from said hand holder.

10

10. The cutter according to claim 9 where said means for firmly attaching said blade hold to said frame further comprising said frame and said blade holder being injected molded in a single operation.

11. The cutter according to claim 9 further comprising an overall size allowing easy storage in a coat pocket.